

SO 90 - 单排

SO90 - S

型号 / Model		SO90 1MSC		SO90 1MSD		SO90 1MSE	
风机 Fan		1 x Ø 910		1 x Ø 910		1 x Ø 910	
6PH/6PL	绕线 Wiring	6PH	6PL	6PH	6PL	6PH	6PL
	换热量 R404A kW	106	89	118	98	128	106
	风量 Airflow m³/h	26125	20405	27490	21395	28235	22110
	声压级 Sound dB(A) 10m	55	47	55	47	55	47
	能效等级 Energy	D	C	C	C	C	C
	inlet diameter 进气管	1"3/8		1"5/8		1"5/8	
	outlet diameter 出液管	1"3/8		1"5/8		1"5/8	
	8PH/8PL	绕线 Wiring	8PH	8PL	8PH	8PL	8PH
换热量 R404A kW		88	73	96	79	104	85
风量 Airflow m³/h		20240	15455	20900	15950	21560	16445
声压级 Sound dB(A) 10m		46	36	45	36	45	36
能效等级 Energy		B	A	B	A	B	A
inlet diameter 进气管		1"3/8		1"3/8		1"3/8	
outlet diameter 出液管		1"3/8		1"3/8		1"3/8	
12PH/12PL		绕线 Wiring	12PH	12PL	12PH	12PL	12PH
	换热量 R404A kW	63	48	68	51	73	55
	风量 Airflow m³/h	12650	8800	13035	9135	13530	9515
	声压级 Sound dB(A) 10m	34	26	34	26	34	26
	能效等级 Energy	A	A	A	A	A	A
	inlet diameter 进气管	1"1/8		1"1/8		1"3/8	
	outlet diameter 出液管	1"1/8		1"1/8		1"3/8	
	表面积 Surface m²	195		244		293	
制冷剂回路体 Circuit volume dm³	29		38		44		
净重 (无制冷) Empty net weight kg	251		289		319		
尺寸 Dimensions	A	mm	1918		2293		2668
	C	mm	1564		1939		2314

尺寸数据公差为+/-10mm.重量数据公差为+/-15kg,具体数值和所选的配件选项有关。

Dimension data are given with +/-10mm tolerance.Weights are given with +/-15kg tolerance.

SINGLE ROW

SO90 2MSC		SO90 2MSD		SO90 2MSE		SO90 3MSC		SO90
2 x Ø 910		2 x Ø 910		2 x Ø 910		3 x Ø 910		3 x Ø
6PH	6PL	6PH	6PL	6PH	6PL	6PH	6PL	6PH
212	177	235	196	255	212	317	266	353
52250	40810	54980	42790	56470	44220	78375	61215	82470
58	50	57	50	57	50	59	52	59
D	C	C	C	C	C	D	C	C
2"1/8		2"1/8		2"1/8		2"1/8		2"
2"1/8		2"1/8		2"1/8		2"1/8		2"
8PH	8PL	8PH	8PL	8PH	8PL	8PH	8PL	8PH
176	145	192	157	208	170	264	217	288
40480	30910	41800	31900	43120	32890	60720	46365	62700
48	39	48	39	48	39	50	41	50
B	A	B	A	B	A	B	A	B
2"1/8		2"1/8		2"1/8		2"1/8		2"
2"1/8		2"1/8		2"1/8		2"1/8		2"
12PH	12PL	12PH	12PL	12PH	12PL	12PH	12PL	12PH
126	96	136	103	146	110	189	144	204
25300	17600	26070	18270	27060	19030	37950	26400	39105
37	29	37	29	37	28	39	30	39
A	A	A	A	A	A	A	A	A
1"5/8		1"5/8		1"5/8		2"1/8		2"
1"5/8		1"5/8		1"5/8		2"1/8		2"
390		488		586		586		73
60		72		85		87		10
469		542		610		681		79
3420		4170		4920		4921		60
3066		3816		4566		4567		56

and may vary depending on chosen options.

3MSD
1910
6PL
294
64185
51
C
1/8
1/8
8PL
236
47850
40
A
1/8
1/8
12PL
155
27405
30
A
1/8
1/8
32
35
34
46
92